



NC110XB Security Camera

Now with Microphone, SD card slot and locking mechanism on housing. Installers recommended adjusted field of view to limit resolution wastage on wider angles, such as walls and sky.

5
MEGA
PIXELS

2.8mm
LENS

PIR

Specifications

Camera Type	Dome
Image Sensor	1/2.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	5
Maximum Video Resolution	2592 x 1944
Lens	2.8 mm (H.FOV: 99°)
Lens Type	Fixed
Maximum Night IR Distance (M)	30
Image clarity	3.5
Connectors	RJ-45
Video Compression	H.265, H.264
ONVIF (depends on firmware version)	ONVIF (Profile S/G/T)
Operating Environment	-30 to +55°C/less than ≤ 95% RH
Dimensions	100x100 mm
Weight (Net)	0.4
Accessories	IV2422X, IV2433X, IV2444X, IV2455X
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	<7W
Connectors (web)	RJ-45 , DC Power Input
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Frame Rate at Resolution	20
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
Edge Recording slot microSD/SDHC Card	Yes
Video Compression	H.265, H.264 (3 streams)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code)
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app
Power Over Ethernet	Yes
Ethernet	Ethernet (10/100 Base-T)
UPNP	Yes
In The Box	Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs
Warranty	3 Year Parts & Labour Warranty
Weight (Packaged)	0.55