



NC-1250B Security Camera

An excellent addition to the ivSEC bullet range of CCTV cameras, this camera uses a separate AI chipset to enhance the processing of more demanding applications.

12
MEGA
PIXELS

3.6mm
LENS

ADVANCED
DETERRENT

Specifications

Camera Type	Bullet
Image Sensor	1/2.3" Progressive CMOS
Maximum Video Resolution (Megapixels)	12
Maximum Video Resolution	4096 x 3072
Frames Per Second (FPS)	15 (12MP) 25 (up to 8MP)
Lens	3.6mm (H.FOV 87°)
Lens Type	Fixed
Maximum Night IR Distance (M)	25
LED	IR, Red & Blue, White
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G/T)
Accessories	IV2422X, IV2433X, IV2444X, IV2447X, IV2455X
Outdoor Use	Yes
IP Rating	IP67
Vandal Resistant	Yes
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Face Detection, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, Rare Sound Detection
Edge Recording microSD/SDHC Card	Micro SD Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	IPv4/IPv6, HTTP, HTTPS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP/IP, DHCP
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud option (camera only)	Dropbox
Audio Streaming	Yes (microphone and speaker built in)
Ethernet	Ethernet (10/100 Base-T)
Power Over Ethernet	Yes (microphone and speaker built in)
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	< 14W
Connectors	RJ-45, DC Power Input
Operating Environment	-35~+60°C/less than ≤ 95% RH
In The Box	Free Software available from FTP, Printed quick user guide, installation template, mounting screws and plugs
Product Dimensions (H x W x L) mm	100 x 100 x 150
Packaging Dimensions (H x W x L) mm	120 x 120 x 200
Weight (Net) kg	0.44
Weight (Gross) kg	0.60
Warranty	3 Year Warranty