



NC110ADX Security Camera

This wide-angle lens camera is perfect for most locations. Includes Advanced Deterrent features - red/blue strobing lights and siren: Speak to talk through the mobile app or set off the siren, full colour at night, robust metal housing, quality AI for Human and Vehicle Detection - a step-up from standard Smart Motion Detection with greater range of detection and reduced false notifications.

5
MEGA
PIXELS

2.8mm
LENS

ADVANCED
DETERRENT

Specifications

Camera Type	Turret
Image Sensor	1/2.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	5
Maximum Video Resolution	2880 x 1620
Frames Per Second (FPS)	25
Lens	2.8 mm (H.FOV: 110°)
Lens Type	Fixed
Maximum Night IR Distance (M)	25
LED	IR, Red & Blue, White
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G/T)
Accessories	IV2422X, IV2477X, IV2433X, IV2444X, IV2455X, IV2457X
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Day/Night Mode	Full color (Auto)
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Perimeter Intrusion Detection, Face Recognition, Human & Vehicle Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection, Rare sound detection
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud option (camera only)	Dropbox
Audio Streaming	Yes (microphone and speaker included)
Ethernet	Ethernet (10/100 Base-T)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	< 4.2W
Connectors	RJ-45, DC Power Input, Reset Button
Operating Environment	-35°C to 60°C (31°F-140°F) Humidity: 20%-95% RH
In The Box	Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs
Product Dimensions (H x W x L) mm	100 x 100 x 100
Packaging Dimensions (H x W x L) mm	120 x 140 x 140
Weight (Net) kg	0.43
Weight (Gross) kg	0.53
Warranty	3 Year Warranty