



NC340ADX Security Camera

The NC340ADX, a formidable turret-style camera, integrates advanced active deterrent functions with cutting-edge surveillance technology. Its 1/2.3" Progressive CMOS sensor captures high-resolution video up to 12 megapixels, ensuring crystal-clear imagery. With a 3.6 mm fixed lens offering an expansive 87° horizontal field of view, it delivers comprehensive coverage for monitoring applications.

12
MEGA
PIXELS

3.6mm
LENS

ADVANCED
DETERRENT

Specifications

Camera Type	Turret
Image Sensor	1/2.3" Progressive CMOS
Maximum Video Resolution (Megapixels)	12
Maximum Video Resolution	4096 × 3072
Frames Per Second (FPS)	15
Lens	3.6mm
Lens Type	Fixed
Maximum Night IR Distance (M)	30
LED	IR, Red & Blue, White
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G/T)
Accessories	IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X
Outdoor Use	Yes
IP Rating	IP67
Vandal Resistant	Yes (IK10)
Day/Night Mode	Auto
Image Enhancement	Smart IR, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Human and vehicle detection, Face Detection, Cross Counting, Crowd Density Detection, Queue Length Detection, Heatmap
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, PPPoE
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud option (camera only)	Dropbox
Audio Streaming	Yes (microphone and speaker included)
Ethernet	Ethernet (10/100/1000 Base-T)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3at, DC12V, AC24V
Power Consumption	< 14W
Connectors	RJ-45, DC Power Input, Analog Video Output, Audio In, Audio Out, Alarm in or out *4.
Operating Environment	-30°C to 55°C (-22°F- 131°F) Humidity: ≤95% RH
In The Box	Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs
Product Dimensions (H x W x L) mm	100 x 100 x 100
Packaging Dimensions (H x W x L) mm	120 x 130 x 130
Weight (Net) kg	0.50
Weight (Gross) kg	0.90
Warranty	3 Year Warranty