



## NC512XD-BLK Security Camera

SONY Sensor. The best dome to capture the event. If it is critical to get the right shot use the motorised lens and 8MP for digital zoom. 25 FPS for smooth footage and the SONY image sensor make this high-end camera great for POS/Cash and entryways. This camera has all the latest AI -



### Specifications

<b>Camera Type</b>	Turret
<b>Image Sensor</b>	1/2.5" Progressive CMOS
<b>Maximum Video Resolution (Megapixels)</b>	8
<b>Maximum Video Resolution</b>	3840 x 2160
<b>Frames Per Second (FPS)</b>	25
<b>Lens</b>	2.7-13.5mm (H.FOV: 111-33°)
<b>Lens Type</b>	Motorised Zoom
<b>Maximum Night IR Distance (M)</b>	45
<b>LED</b>	IR
<b>Video Compression</b>	H.265+, H.265, H.264+, H.264, MJPEG
<b>ONVIF depends on firmware version</b>	ONVIF (Profile S/G/T) 21.12 or greater, HTTP API
<b>Accessories</b>	IV2422X, IV2433X, IV2444X, IV2455X
<b>Outdoor Use</b>	Yes
<b>IP Rating</b>	IP67
<b>Vandal Resistant</b>	Yes
<b>Day/Night Mode</b>	Auto
<b>Image Enhancement</b>	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
<b>Intelligent Video (IVS)</b>	Perimeter Intrusion Detection, Face Recognition, Human & Vehicle Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection, Rare sound detection
<b>Edge Recording microSD/SDHC Card</b>	Micro SD/SDHC Card
<b>Multiple Streams (encode format)</b>	3 Streams
<b>Software</b>	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
<b>Protocols</b>	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPoE, UPNP, SMTP, SMTP, P2P (QR code)
<b>Language</b>	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
<b>Cloud option (camera only)</b>	Dropbox
<b>Audio Streaming</b>	Yes - input connector for external mic
<b>Ethernet</b>	Ethernet (10/100 Base-T)
<b>Power Over Ethernet</b>	Yes
<b>Power Supply</b>	Power over Ethernet IEEE 802.3af, DC12V
<b>Power Consumption</b>	< 9W
<b>Connectors</b>	RJ-45, DC Power Input, Analog Video Output, Audio In, Audio Out, Alarm in or out *4, Reset Button
<b>Operating Environment</b>	-30~+55°C/less than ≤ 95% RH
<b>In The Box</b>	Free Software available from FTP, Printed quick user guide, installation template, mounting screws and plugs
<b>Product Dimensions (H x W x L) mm</b>	113 x 151 x 151
<b>Packaging Dimensions (H x W x L) mm</b>	150 x 170 x 170
<b>Weight (Net) kg</b>	0.87
<b>Weight (Gross) kg</b>	1.00
<b>Warranty</b>	3 Year Warranty