



Specifications

Camera Type PTZ Image Sensor 1/2.7" Progressive CMOS Maximum Video Resolution (Megapixels) 5 Frames Per Second (FPS) 30 Lens 5.0mm − 125mm (H.FOV: 53.3 to 3.8") Lens Type Motorised Pan, Titl and Zoom Maximum Night IR Distance (M) 100 LED IR Video Compression H. 265+, H. 265, H. 264+, H. 264, M.PEG ONVIF depends on firmware version ONIVIF (Profile S/G/T) 21.12 or greater, HTTP API Accessories IV2488X Outdoor Use Yes IP Rating IP67 Vandal Resistant Yes Day/Night Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Detog, 30 Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Gueve Length Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Detection, Stationary Object Detection, Stationary Object Detection, Stationary		
Maximum Video Resolution (Megapixels) 5 Maximum Video Resolution 2880 x 1620 Frames Per Second (FPS) 30 Lens 5.0mm - 125mm (H.FOV: 53.3 to 3.8°) Lens Type Motorised Pan, Tilt and Zoom Maximum Night IR Distance (M) 100 LED IR Video Compression H.265+, H.265, H.264+, H.264, MJPEG ONVIF depends on firmware version ONVIF (Profile S/G/T) 2.1.12 or greater, HTTP API Accessories Yes Utdoor Use Yes IP Rating IP67 Vandal Resistant Yes Day/Night Mode Auto Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Edge Recording microSD/SDHC Card Micro SD/SDHC Card Micro SD/SDHC Card Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPDE, UPNP, SMTP, PPTP, PPTP (QR code)	Camera Type	
Maximum Video Resolution 2880 x 1620 Frames Per Second (FPS) 30 S.Dmm -125mm (H.FOV: 53.3 to 3.8°) Lens Type Motorised Pan, Tilt and Zoom Maximum Night IR Distance (M) 100 LED IR Video Compression H. 265+, H. 265, H. 264+, H. 264, MJPEG ONVIF depends on firmware version ONVIF (Profile S/G/T) 21.12 or greater, HTTP API Accessories V2488X Outdoor Use Yes PRating IP67 Vandal Resistant Yes Outdoor Use Tilt mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 30 Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Price Received From the Video (IVS) Streams As Streams Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) From Cloud option (camera only) Power Over Ethernet Ethernet Ethernet Ethernet 1160 Base -T Power Over Ethernet Ethernet Ethernet 1160 Base -T Power Over Ethernet Product Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Net) kg 3.00		<u> </u>
Frames Per Second (FPS) Lens 5.0mm - 125mm (H.F.OV: 53.3 to 3.8°) Lens Type Motorised Pan, Tilt and Zoom Maximum Night IR Distance (M) LED IR Video Compression NL 265+, H.265, H.264+, H.264, MJPEG ONVIF depends on firmware version ONVIF (Profile S/G/T) 21.12 or greater, HTTP API Accessories IV2488X Outdoor Use Yes IP Rating IP 67 Vandal Resistant Ves Day/Night Mode Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Multiple Streams (encode format) Software Device Search/Conding Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DNS, NTP, PPPDE, UPNP, SMTP, PPP (QR code) English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Herberw, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Over Ethernet Yes Power Over Ethernet Yes Power Over Ethernet Yes Power Over Ethernet The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.000 Weight (Net) kg 3.00	Maximum Video Resolution (Megapixels)	5
Lens Type Motorised Pan, Tilt and Zoom Maximum Night IR Distance (M) 100 LED IR Video Compression H. 265+, H.265, H.264+, H.264, MJPEG ONVIF (Profile S/G/T) 21.12 or greater, HTTP API Accessories IV2488X Outdoor Use Yes IP Rating IP67 Vandal Resistant Yes IP Rating IP67 Vandal Resistant Yes IP Mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Usersee Plate Detection Edge Recording microSD/SDHC Card Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPDE, UPNP, SMTP, SMTP, PSP (QR code) Protocols TcP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPDE, UPNP, SMTP, PSP (QR code) Protocols TcP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPDE, UPNP, SMTP, PSP (QR code) Cloud option (camera only) Dropbox Audio Streaming Tensional Contract	Maximum Video Resolution	2880 x 1620
Lens Type Maximum Night IR Distance (M) 100 LED IR Video Compression H.265+, H.265, H.264+, H.264, MJPEG ONVIF depends on firmware version ONVIF (Profile Sr/JT) 21.12 or greater, HTTP API Accessories IV248BX Outdoor Use Yes IP Rating IP67 Vandal Resistant Yes Day/Night Mode Auto Image Enhancement Flüp mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flüp, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Venicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TcP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, PPP (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet (Drillo Base-T) Power Over Ethernet Ethernet (Tol/100 Base-T) Power Over Ethernet Ethernet (Tol/100 Base-T) Power Over Ethernet Power Supply Power over Ethernet IEEE 802.3at, DC12V Power Consumption <14W x L) mm 455 x 330 x 380 Product Dimensions (H x W x L) mm 455 x 330 x 380 Poduct Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Gross) kg 3.00	Frames Per Second (FPS)	30
Maximum Night IR Distance (M) IR Video Compression H. 265+, H.265, H.265, H.264+, H.264, MJPEG ONVIF depends on firmware version ONVIF (Profile S/G/T) 21.12 or greater, HTTP API Accessories IV2480X Outdoor Use Yes IP Rating IP67 Vandal Resistant Ves Day/Night Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Erime Plate Detection Multiple Streams (encode format) 3 Streams Oevice Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocots TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) Froglosh, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Power Over Ethernet Yes Power Consumption Al45 Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment - 20°C to 60°C (14°F-140°F) Humidity: 70% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (Hx W x L) mm 455 x 330 x 380 Weight (Gross) kg Weight (Gross) kg 3.00	Lens	5.0mm -125mm (H.FOV: 53.3 to 3.8°)
LED Video Compression H.265+, H.265+, H.264+, H.264, MJPEG ONVIF depends on firmware version ONVIF (Profile S/G/T) 21.12 or greater, HTTP API Accessories IV2488X Outdoor Use Yes IP67 Vanda Resistant Yes Day/Night Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Wehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Uneue Length Detection, License Plate Detection Micro SD/SDHC Card Muttiple Streams (encode format) Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPDE, LUPNP, SMTP, PZP (QR code) English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power Over Ethernet Teherost (14W Connectors R] -45, DC Power Input, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment - 20°C to 60°C (14°-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 3.00	Lens Type	Motorised Pan, Tilt and Zoom
Video Compression	Maximum Night IR Distance (M)	100
ONVIF (Profile S/G/T) 21.12 or greater, HTTP API Accessories IV2488X Outdoor Use Yes IP Rating IP67 Vandal Resistant Yes Outy Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heal Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, PZP (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Consumption Yes Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment - 20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Ret) kg Weight (Gross) kg 3.00	LED	IR
Accessories Outdoor Use Yes PRating IP67 Vandal Resistant Yes Day/Night Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Perimeter Intrusion Detection, Line Crossing Detection, Perimeter Intrusion Detection, Line Crossing Detection, Perimeter Intrusion Detection, Detection, Perimeter Intrusion Detection, Detection, Perimeter Intrusion Detection, Line Crossing Counting, Heat Map, Crowd Density Detection, Crowd Density Detection, Crossing Counting, Heat Map, Crowd Density Detection,	Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
Outdoor Use Yes IPRating IP67 Vandal Resistant Yes Day/Night Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Edge Recording microSD/SDHC Card Micro SD/SDHC Card Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebry, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Consumption < 14W	ONVIF depends on firmware version	ONVIF (Profile S/G/T) 21.12 or greater, HTTP API
PRating	Accessories	IV2488X
Vandal Resistant Yes Day/Night Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Edge Recording microSD/SDHC Card Micro SD/SDHC Card Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Consumption < 14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot.	Outdoor Use	Yes
Day/Night Mode Auto Image Enhancement Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Intelligent Video (IVS) Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Oueue Length Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Edge Recording microSD/SDHC Card Micro SD/SDHC Card Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Consumption < 1/4W	IP Rating	IP67
Image Enhancement	Vandal Resistant	Yes
White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Mutiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power over Ethernet IEEE 802.3at, DC12V Power Consumption <14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm Weight (Net) kg Weight (Gross) kg 3.00	Day/Night Mode	Auto
Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection Edge Recording microSD/SDHC Card Micro SD/SDHC Card Micro SD/SDHC Card Micro SD/SDHC Card Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPDE, UPNP, SMTP, SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Over Ethernet Yes Power Consumption <14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Image Enhancement	
Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power over Ethernet IEEE 802.3at, DC12V Power Consumption < 14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (Hx W x L) mm 455 x 330 x 380 Weight (Gross) kg 3.00	Intelligent Video (IVS)	Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detec-
Multiple Streams (encode format) 3 Streams Software Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) Protocols TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power over Ethernet IEEE 802.3at, DC12V Power Consumption < 14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (Hx W x L) mm 455 x 330 x 380 Weight (Gross) kg 3.00	Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, PPP (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power over Ethernet IEEE 802.3at, DC12V Power Consumption <14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00		3 Streams
SMTP, P2P (QR code) Language English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Dropbox Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power over Ethernet IEEE 802.3at, DC12V Power Consumption <14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
brew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish Cloud option (camera only) Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power over Ethernet IEEE 802.3at, DC12V Power Consumption < 14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Protocols	
Audio Streaming Yes - input connector for external mic, input connector for external speaker Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power Consumption < 14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Language	
Ethernet Ethernet (10/100 Base-T) Power Over Ethernet Yes Power Supply Power consumption <14W Connectors RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Cloud option (camera only)	Dropbox
Power Over EthernetYesPower SupplyPower over Ethernet IEEE 802.3at, DC12VPower Consumption< 14W	Audio Streaming	Yes - input connector for external mic, input connector for external speaker
Power SupplyPower over Ethernet IEEE 802.3at, DC12VPower Consumption< 14W	Ethernet	Ethernet (10/100 Base-T)
Power Consumption< 14WConnectorsRJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot.Operating Environment-20°C to 60°C (14°F-140°F) Humidity: 90% RHIn The BoxFree Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugsProduct Dimensions (H x W x L) mm455 x 330 x 380Packaging Dimensions (H x W x L) mm455 x 330 x 380Weight (Net) kg2.00Weight (Gross) kg3.00	Power Over Ethernet	Yes
Connectors RJ-45, DC Power Input, Audio Out, Alarm in or out *1, reset button, SD card slot. Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Power Supply	Power over Ethernet IEEE 802.3at, DC12V
Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Power Consumption	<14W
Operating Environment -20°C to 60°C (14°F-140°F) Humidity: 90% RH In The Box Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Connectors	RJ-45, DC Power Input, Audio In, Audio Out, Alarm in or out *1, reset button, SD card slot.
Screws and plugs	Operating Environment	
Product Dimensions (H x W x L) mm 455 x 330 x 380 Packaging Dimensions (H x W x L) mm 455 x 330 x 380 Weight (Net) kg 2.00 Weight (Gross) kg 3.00	In The Box	
Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Product Dimensions (H x W x L) mm	
Weight (Net) kg 2.00 Weight (Gross) kg 3.00	Packaging Dimensions (H x W x L) mm	455 x 330 x 380
Weight (Gross) kg 3.00		2.00
		3.00
		3 Year Warranty