



NC340XB Security Camera

12.3° Progressive CMOS image sensor, it boasts a maximum video resolution of 12 megapixels, delivering risp and detailed forotage. Its 35 mm fixed lens with a horizontal field of view of 37° mesures wide coverage, the its maximum night IR distance of 30 meters guarantees clear monitoring even in low-light conditions. quipped with advanced video compression technology including H 265+ and H 264. He NC340XB primose shore paper with advances of video compression technology including H 265+ and H 264. He NC340XB primose shore pape without compromising on video public, IRs ONUF compatibility ensures seamless treatments with various surveillance systems, while its IP66 rating makes it suitable for outdoor use, we in harsh weather conditions.

With intelligent video features such as perimeter infrusion detection, line crossing detection, and face betection, the KCANS enhances exertify surveillance capabilities. Additionally, its support for audo streaming and edge recording via microSD card provides flexibility in data storage and audo monitoring. This camera also offers various image enhancement options and supports multiple steams for versatile indoe streaming. With Power over Ethernet capability and Ethernet connectivity, instalation and setup part streaming. More than the KC340X Economic with a comprehensive warranty and includes essential cocessories for easy installation, making it a reliable choice for professional surveillance applications ration and the surveil streaming and the surveil surveillance and professional surveillance applications rations and the surveillance applications and surveillance applications rations and the surveillance applications and surveillance applications rations and the surveillance applications and surveillance applications rations and the surveillance applications rations applications applications rations applications rations applications applications applications rations applications applications applications rations applications applications applications rations applications applications rations applications applications applications applications applications rations applications applications rations applications applications rations applications applications applications applications applications applications applications rations applications applicati



Specifications

| Camera Type | Turret |
|---------------------------------------|--|
| Image Sensor | 1/2.3" Progressive CMOS |
| Maximum Video Resolution (Megapixels) | 12 |
| Maximum Video Resolution | 4512 x 2512 |
| Frames Per Second (FPS) | 15 |
| Lens | 3.6 mm (H.FOV: 87°) |
| Lens Type | Fixed |
| Maximum Night IR Distance (M) | 30 |
| LED | IR |
| Video Compression | H.265+, H.265, H.264+, H.264, MJPEG |
| ONVIF depends on firmware version | ONVIF (Profile S/G/T) 21.12 or greater, HTTP API |
| Accessories | IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X |
| Outdoor Use | Yes |
| IP Rating | IP67 |
| Vandal Resistant | Yes |
| Day/Night Mode | Auto |
| Image Enhancement | Smart IR, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction |
| Intelligent Video (IVS) | Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Human and vehicle detection, Face Detection, Cross Counting, Crowd Density Detection, Queue Length Detection, Heatmap |
| Edge Recording microSD/SDHC Card | Micro SD/SDHC Card |
| Multiple Streams (encode format) | 3 Streams |
| Software | Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) |
| Protocols | TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code) |
| Language | English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, He- brew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish |
| Cloud option (camera only) | Dropbox |
| Audio Streaming | Yes (microphone included) |
| Ethernet | Ethernet (10/100 Base-T) |
| Power Over Ethernet | Yes |
| Power Supply | Power over Ethernet IEEE 802.3af, DC12V |
| Power Consumption | < 7W |
| Connectors | RJ-45, DC Power Input, Reset Button |
| Operating Environment | -30~+55°C/less than ≤ 95% RH |
| In The Box | Free Software available from FTP, Printed quick user guide, installation template, mounting screws and plugs |
| Product Dimensions (H x W x L) mm | 100 x 100 x 100 |
| Packaging Dimensions (H x W x L) mm | 120 x 130 x 130 |
| Weight (Net) kg | 0.50 |
| Weight (Gross) kg | 0.90 |
| Warranty | 3 Year Warranty |
| | |