



NC340ADXB Security Camera

The NC340ADXB, a formidable turret-style camera, integrates advanced active deterrent functions with cutting-edge surveillance technology. Its 1/2.3" Progressive CMOS sensor captures high-resolution video up to 12 megapixels, ensuring crystal-clear imagery. With a 3.6 mm fixed lens offering an expansive 87° horizontal field of view, it delivers comprehensive coverage for monitoring applications.

This camera is equipped with powerful active deterrent features, enhancing its security capabilities. Alongside intelligent video analytics like perimeter intrusion detection and face detection, it incorporates active deterrence functions such as audible warnings and strobe lights to deter potential threats effectively.

Designed for versatility and reliability, the NC340ADXB supports audio streaming and edge recording via microSD card, allowing for seamless integration into various surveillance setups. Its IP66 rating ensures durability in outdoor environments, while H.265+ and H.264 video compression technologies optimize storage space without compromising video quality.

With Power over Ethernet capability and Ethernet connectivity, installation is simplified, making it suitable for a wide range of surveillance applications. Backed by a comprehensive warranty and equipped with essential accessories, the NC340ADXB offers unparalleled security and peace of mind in professional surveillance environments.

12
MEGA
PIXELS

3.6mm
LENS

**ADVANCED
DETERRENT**

Specifications

Camera Type	Turret
Image Sensor	1/2.3" Progressive CMOS
Maximum Video Resolution (Megapixels)	12
Maximum Video Resolution	4512 x 2512
Frames Per Second (FPS)	15
Lens	3.6 mm (H.FOV: 87°)
Lens Type	Fixed
Maximum Night IR Distance (M)	30
LED	IR, Red & Blue, White
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G/T)
Accessories	IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes (IK10)
Day/Night Mode	Auto
Image Enhancement	Smart IR, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Human and vehicle detection, Face Detection, Cross Counting, Crowd Density Detection, Queue Length Detection, Heatmap
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, PPPoE
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud option (camera only)	Dropbox
Audio Streaming	Yes (microphone and speaker included)
Ethernet	Ethernet (10/100)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3at, DC12V
Power Consumption	< 14W
Connectors	RJ-45, DC Power Input
Operating Environment	-30°C to 55°C (-22°F - 131°F) Humidity: ≤95% RH
In The Box	Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs
Product Dimensions (H x W x L) mm	100 x 100 x 100
Packaging Dimensions (H x W x L) mm	120 x 130 x 130
Weight (Net) kg	0.50
Weight (Gross) kg	0.90
Warranty	3 Year Warranty