



NC541XA Security Camera

SONY sensor, 360-degree view. Great for the center of a room. Has a microphone and speaker built-in.

9
MEGA
PIXELS

2mm
LENS

SONY
STARVIS
SENSOR

Specifications

Camera Type	Fisheye
Image Sensor	1/1.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	9
Maximum Video Resolution	3000 x 3000
Frames Per Second (FPS)	25
Lens	2mm (H.FOV 360°)
Lens Type	Fixed
Maximum Night IR Distance (M)	5
LED	IR
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G)
Accessories	n/a
Outdoor Use	Yes
IP Rating	IP66
IK Rating	IK10
Day/Night Mode	Auto
Image Enhancement	Fisheye ceiling/desktop/wall/tilt, VR, cylinder, Panorama 180, Panorama 360, 4PTZ, Fisheye+3PTZ, Fisheye+8PTZ, 3 Panorama 360 PTZ, 8 Panorama 360 PTZ, Rotate, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
Intelligent Video (IVS)	Motion Detection
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPoE, UPNP, SMTP, SMTP, P2P (QR code)
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud option (camera only)	Dropbox
Audio Streaming	Yes (microphone and speaker included)
Ethernet	Ethernet (10/100 Base-T)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	< 7W
Connectors	RJ-45, Analog Video Out, Audio In, Audio Out, Alarm in or out *4
Operating Environment	-30~+55°C/less than ≤ 95% RH
In The Box	Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs
Product Dimensions (H x W x L) mm	55 x 120 x 120
Packaging Dimensions (H x W x L) mm	100 x 150 x 150
Weight (Net) kg	0.40
Weight (Gross) kg	0.50
Warranty	3 Year Warranty