



Specifications

amera Type	Turret
nage Sensor	1/2.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	8
Maximum Video Resolution	3840 x 2160
rames Per Second (FPS)	15
ens	_2.8 mm (H.FOV: 106°)
ens Type	Fixed
Maximum Night IR Distance (M)	25
ED	IR, Red & Blue, White
ideo Compression	H.265+, H.265, H.264+, H.264, MJPEG
NVIF depends on firmware version	ONVIF (Profile S/G/T) 21.12 or greater, HTTP API
ccessories	IV2422X, IV2477X, IV2433X, IV2444X, IV2455X, IV2457X
Outdoor Use	Yes
Rating	IP67
(Rating	IK08
ay/Night Mode	Full color (Auto)
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White
	Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
ntelligent Video (IVS)	Smart Motion Detection, Perimeter Intrusion Detection, Line Crossing Detection
dge Recording microSD/SDHC Card	Micro SD/SDHC Card
/ultiple Streams (encode format)	2 Streams
oftware	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P
	(QR code)
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew,
	Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
loud option (camera only)	Dropbox
udio Streaming	Yes (microphone and speaker included)
thernet	Ethernet (10/100 Base-T)
ower Over Ethernet	Yes
ower Supply	Power over Ethernet IEEE 802.3af, DC12V
ower Consumption	<7W
onnectors	RJ-45, DC Power Input, Reset Button
perating Environment	-30~+55°C/less than ≤ 95% RH
n The Box	Printed quick user guide, installation template, mounting screws and plugs
roduct Dimensions (H x W x L) mm	90 x 100 x 100
ackaging Dimensions (H x W x L) mm	120 x 135 x 135
Veight (Net) kg	0.22
Veight (Gross) kg	0.55
Varranty	3 Year Warranty