



NC368ADX Security Camera

Full colour at night. Improvements have been made to the image sensor -1/1.8 enlarged image sensor enables more light to be gathered. Together with built-in warm-light LEDs, this creates an excellent full colour image. Quality AI for Human and Vehicle Detection -a step-up from standard Smart Motion Detection with greater range of detection and reduced false notifications.

8
MEGA
PIXELS

2.8mm
LENS

112°
FOV

Specifications

Camera Type	Turret
Image Sensor	1/1.8" Progressive CMOS
Maximum Video Resolu8on (Megapixels)	8
Maximum Video Resolu8on	3840 x 2160
Frames Per Second (FPS)	15
Lens	2.8 mm (H.FOV: 112°)
Lens Type	Fixed
Maximum Night IR Distance (M)	N/A
LED	Warm White, Red & Blue
Video Compression	H.265, H.264 H.265+, H.264+, MJPGE
ONVIF depends on firmware version	ONVIF (Profile S/G/T) 21.12 or greater, HTTP API
Accessories	IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X
Outdoor Use	Yes
IP Rating	IP67
IK Rating	IK10
Day/Night Mode	Schedule (Time Based), Full colour or Day/Night (Warm White LEDs)
Image Enhancement	Smart IR, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shuber, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Face Recognition, Human&Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Cross Counting, Stationary Object Detection, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection, Rare Sound Detection
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud op8on (camera only)	Dropbox
Audio Streaming	Yes (microphone and speaker included)
Ethernet	Ethernet (10/100 Base-T)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consump8on	< 5.4W
Connectors	RJ-45, DC Power Input, Reset Bubon
Opera8ng Environment	-30°C to 55°C (-22°F-131°F) Humidity: 20%-80% RH
In The Box	Free Software available from FTP, Printed quick user guide, installation template, mounting screws and plugs
Product Dimensions (H x W x L) mm	98 x 115 x 115
Packaging Dimensions (H x W x L) mm	130 x 160 x 160
Weight (Net) kg	0.40
Weight (Gross) kg	0.60
Warranty	3 Year Warranty