



NC340ADX Security Camera

The NC340ADX, a formidable turret-style camera, integrates advanced active deterrent functions with cutting-edge surveillance technology. Its 1/2.3" Progressive CMOS sensor captures high-resolution video up to 12 megapixels, ensuring crystal-clear imagery. With a 3.6 mm fixed lens offering an expansive 87° horizontal field of view, it delivers comprehensive coverage for monitoring applications.

12
MEGA
PIXELS

3.6mm
LENS

ADVANCED
DETERRENT

Specifications

| | |
|--|--|
| Camera Type | Turret |
| Image Sensor | 1/2.3" Progressive CMOS |
| Maximum Video Resolution (Megapixels) | 12 |
| Maximum Video Resolution | 4096 × 3072 |
| Frames Per Second (FPS) | 15 |
| Lens | 3.6mm |
| Lens Type | Fixed |
| Maximum Night IR Distance (M) | 30 |
| LED | IR, Red & Blue, White |
| Video Compression | H.265+, H.265, H.264+, H.264, MJPEG |
| ONVIF depends on firmware version | ONVIF (Profile S/G/T) |
| Accessories | IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X |
| Outdoor Use | Yes |
| IP Rating | IP67 |
| Vandal Resistant | Yes (IK10) |
| Day/Night Mode | Auto |
| Image Enhancement | Smart IR, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction |
| Intelligent Video (IVS) | Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Human and vehicle detection, Face Detection, Cross Counting, Crowd Density Detection, Queue Length Detection, Heatmap |
| Edge Recording microSD/SDHC Card | Micro SD/SDHC Card |
| Multiple Streams (encode format) | 3 Streams |
| Software | Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, PPPoE |
| Language | English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish |
| Cloud option (camera only) | Dropbox |
| Audio Streaming | Yes (microphone and speaker included) |
| Ethernet | Ethernet (10/100/1000 Base-T) |
| Power Over Ethernet | Yes |
| Power Supply | Power over Ethernet IEEE 802.3at, DC12V, AC24V |
| Power Consumption | < 14W |
| Connectors | RJ-45, DC Power Input |
| Operating Environment | -30°C to 55°C (-22°F-131°F) Humidity: ≤95% RH |
| In The Box | Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs |
| Product Dimensions (H x W x L) mm | 100 x 100 x 100 |
| Packaging Dimensions (H x W x L) mm | 120 x 130 x 130 |
| Weight (Net) kg | 0.50 |
| Weight (Gross) kg | 0.90 |
| Warranty | 3 Year Warranty |