



NR6324EX NVR

Experience cutting-edge video technology with our 32 channel NVR. Enjoy a 256Mbps bandwidth for all your camera needs, 4 x HDD drive bays allow for plenty of recording retention, holding up to 96TB of footage. Stay in charge and react promptly with remote mobile access. This NVR has many features that are best demonstrated. Please contact us.



Specifications

Maximum Channels	32
Maximum Video Resolution (Megapixels)	12 MP
Examples of Channels at a resolution with FPS	256 MP5
Video Compression	H.264, H.264+, H.265, H.265+
Video Output Resolu2on	8MP, 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Image Display	1, 4, 6, 8, 9, 10, 12, 13, 14, 16, 17, 19, 20, 22, 25, 32
ONVIF depends on firmware version	ONVIF (Profile S/G/T) 21.12 or greater, HTTP API
Intelligent Video (Dependant On Camera)	Perimeter Intrusion Detection, Face Recognition, Human & Vehicle Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection, Rare Sound Detection, Video Tampering, License Plate Recognition
Search Method	Continuous, Scheduling, Event Triggered By IVS filtering. Snapshot Searching, Tagging footage, Time Lapse, Slice (Multiple Snapshot Thumbnail Search Per Hour), General (Indicated Timeline Seach).
Total Storage Potential (TB)	96
HDD Bays, Size	Bays x 4, up to 24TB per HDD
RAID	n/a
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app
Protocols	TCP, IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP, RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code)
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Audio Streaming	Audio out
Non Power Over Ethernet Ports	2
Power Over Ethernet Ports	0
Power Supply	DC 12V, 5A
Power Consumption	12W (Without HDD)
Connectors	HDD: 3.5" SATA HDD Slot x 4, USB2 Female x 2, Gigabit Ethernet: RJ-45 Port x 2, HDMI and VGA, eSata x1, Alarm ports 8 in and 1 out, RS485, Audio out, Power input x 2, On off switch
Operating Environment	-10°C~+50°C (14°F ~ 122°F) Humidity: Less than 90%RH
In The Box	Printed quick installation guide, Mouse, HDD screws, Power supply.
Product Dimensions (H x W x L) mm	66 x 326 x 378
Packaging Dimensions (H x W x L) mm	120 x 380 x 500
Weight (Net) kg	1.30
Weight (Gross) kg	1.60
Warranty	2 Years Parts

All IVSEC X Range Network Video Recorders (NVRs) feature



Plug and Play
with IVSEC X range cameras



ONVIF Profile S/G/T
for ease of IP cameras compatibility on 3rd party recording systems



Powerful H.264, H.265 Compression
to save on hard drive storage



Easy to use Search Methods
search by date/time range, and filter by analytics: PIR detection, IVS, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Face Detection, Line Cross Counting, Human and vehicle tracking *Analytics/IVS is camera dependant



Remote Control
remotely control NVRs and cameras using the free Video Management System (VMS) for PCs, Internet browsers, and powerful mobile applications

<https://ivsecurity.com.au/product/nr6324ex-nvr/>