



NC110XD Security Camera

Now with Microphone, SD card slot and locking mechanism on housing. Installers recommended adjusted field of view to limit resolution wastage on wider angles, such as walls and sky.

5
MEGA
PIXELS

2.8mm
LENS

PIR

Specifications

Camera Type	Turret
Image Sensor	1/2.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	5
Maximum Video Resolution	2592 x 1944
Frames Per Second (FPS)	20
Lens	2.8 mm (H.FOV: 99°)
Lens Type	Fixed
Maximum Night IR Distance (M)	30
LED	IR
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G/T) 21.12 or greater, HTTP API
Accessories	IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X, IV2480X
Outdoor Use	Yes
IP Rating	IP66
IK Rating	IK10
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Motion Detection, PIR, Sounds Detection
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code)
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud option (camera only)	Dropbox
Audio Streaming	Yes (microphone included)
Ethernet	Ethernet (10/100 Base-T)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	< 7W
Connectors	RJ-45, DC Power Input, Reset Button
Operating Environment	-30° +55°C/less than ≤ 95% RH
In The Box	Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs
Product Dimensions (H x W x L) mm	100 x 100 x 100
Packaging Dimensions (H x W x L) mm	120 x 140 x 140
Weight (Net) kg	0.40
Weight (Gross) kg	0.53
Warranty	3 Year Warranty